

TMC 188/40

Four Axis Linear And Rotary Motion Control Module

The TMC 188/40 motion control module is a high performance linear and rotary motion controller for the Simatic TI 505 series Programmable Controllers. Each axis can be independently programmed to use either a quadrature encoder or magnetostrictive linear displacement transducer (Temposonics™) as a position sensing device. Drive outputs can be configured to work with either current or voltage servo drive inputs.

Features

- 4 Magnetostrictive inputs in a single module
- Four axes of independent or coordinated control
- Simatic-TI 505 series compatible
- Motion profiles can be changed on the fly
- Optically isolated inputs and outputs
- Full PID loop control
- Two millisecond control loop
- Front panel status indicators
- Special Function Interface
- Programmed using V Memory
- Direct connection to magnetostrictive transducers (Temposonics)

Applications


- Palletizers/Stackers
- Laser positioning
- Tube forging machines
- Pinch roller positioning
- Robotics
- Headrigs, carriages, and other Forest industry machinery
- Hydraulic actuators
- Servo Motors

Magnetostrictive Inputs

- Resolution to 0.001 inches
- 1,2 or 4 recirculations
- Positive or negative interrogation pulses
- Maximum speeds up to 60 inches per second (240 ips at 0.004" resolution)
- Transducer lengths up to 240 inches (0.004" resolution)

DCSMON Diagnostic Program (requires PC or compatible)

- Provides graphic display of latest motion profile position and velocity information



- Calculates motion parameters SCALE, OFFSET & DIRECTION
- Provides access to auto tuning function
- Allows user to activate simple motion profiles from a keyboard
- Permits user to change control parameters from a keyboard
- Displays parameter and status information for multiple axes
- Saves and retrieves graphic diagnostic information to and from disk

TMC 188/40

Hardware Information

Magnetostrictive Interface

Interface Type	Start/Stop digital pulse
Temposonics I and II	Direct connection
Temposonics II & RPM module	One differential driver board per axis (AMP 10)
Norstat	Direct connection
Balluff	One differential driver board per axis with BTL-2-P
T&R Electronics	One recirculation only (Consult Delta before using)
Input Isolation	2500 VAC optically isolated
Recirculations	Provided by module: 1, 2 or 4 (positive or negative pulse)
Counters	27.75 MHz
Position update rate	Two milliseconds
Sensor protection	4.7 and 15 ohm resistors for sensor power

Drive Outputs

Output Isolation	2500 VAC optically isolated
Current Mode	±25, ±50, ±100 milliamps
Voltage Mode	±2.5, ±5, ±10 Volts
Resolution	12 bit

Simatic TI 505 Interface

WY register requirements	8 WY registers
V Memory requirements	Up to 148 locations
Typical 525 scan times	10 milliseconds per module (plus remote I/O overhead)
Typical 535 scan times	1.6 milliseconds per module (plus remote I/O overhead)
Typical 545 scan times	0.8 milliseconds per module (plus remote I/O overhead)
505 Bus Interface	Special Function Interface Hardware

Power Requirements

TI bus	+ 5 VDC @ 1.500 Amps maximum
External Magnetostrictive sensor	±15 VDC @ 500 mA, +5 VDC @ 500 mA
External drive	±15 VDC @ 500 mA

Mechanical Specifications

Dimensions (WxHxD)	1.6 x 10.5 x 7.5 in (41 x 266 x 191 mm)
Weight	1.3 lb. (592g)
Connectors:	
Backplane	Direct connection to Simatic TI 505 series backplane
Quadrature	DB-37S
Magnetostrictive Sensor	DB-25S
Drive	DB-15S

Environment

Operating Temperature	+32 to +140 F (0 to +60C)
Non-Operating Temperature	-40 to +185 F (-40 to +85C)
Humidity	0 to 95% non-condensing



Programming Parameters

Axis Setup Parameters		
Direction	Scale	Sign of position units with respect to Transducer Counts Conversion from transducer counts to user position units
Offset		Displacement of user zero from transducer zero
Extend Limit		Maximum length allowed
Retract Limit		Minimum length allowed
Static Gain		Proportional gain at rest
Extend Gain		Proportional gain when extending
Retract Gain		Proportional gain when retracting
Extend Feed Forward		Feed forward drive when extending
Retract Feed Forward		Feed forward drive when retracting
Feed Forward Advance		Time shift in milliseconds for Feed Forward term
Hysteresis		Drive deadband compensation
Dither		Static friction compensation
Differential Gain		Differential gain
Integral Gain		Integral gain while in motion
Null Update		Null calculation interval in milliseconds
New Null		Preset drive offset value
Maximum Position Error		Set point for position error indication
Halt Mask		Disable for ramped stop on errors
Emergency Stop Mask		Disable for quick stop on errors
At Commanded Position		Window around requested position for status bit
Near Commanded Position		Window around requested position for status bit

Axis Dynamic Control Parameters		
Mode Bits		Function selection bits
Acceleration		Acceleration rate or distance
Deceleration		Deceleration rate or distance
Maximum Speed		Maximum speed during a move
Requested Position		Destination position in position units
Command		Command to be executed (F, G, H, P, R, S, Z, @) F Auto adjustment of Feed Forward G Move axis H Halt axis O Override/Open loop control P Initialize axis setup parameters R Restore previously saved drive null S Save current drive null

Axis Status Information (Read only)		
Command Position		Requested position with limits checked
Target Position		Calculated position of axis
Actual Position		Measured position
Transducer Counts		Raw transducer counts
Drive Level		Output drive in raw A/D counts
Status Word		Axis error and status bits Bit 01 - Parameters initialized Bit 02 - Lag error Bit 03 - Lead error Bit 04 - Overdrive error Bit 05 - Valve out of null Bit 06 - Transducer not responding Bit 07 - Position overflow Bit 08 - Parameter error Bit 09 - Active (Axis one only) Bit 10 - Stopped Bit 11 - Decelerating Bit 12 - At maximum speed Bit 13 - Accelerating Bit 14 - Halted Bit 15 - Near commanded position Bit 16 - At commanded position



TMC 188/40

Wiring Information

DB15P to pigtail cable (6 feet) for Drive outputs. Cable uses Alpha 1181/15 or equiv.

Pin	Function	Wire Color
1	+15 input	RED
2	Power Supply Common	BLACK
3	-15 input	WHITE
4	Common	GREEN
5	Drive Out 1	ORANGE
6	Common	BLUE
7	Common	BROWN
8	Drive Out 2	YELLOW
9	Common	RED/BLACK
10	Drive Out 4	RED/YELLOW
11	Common	RED/GREEN
12	Common	TAN
13	Drive Out 3	PINK
14	Common	GRAY
15	Common	VIOLET

DB25P to pigtail cable (6 feet) for magnetostrictive sensor inputs . Cable uses Alpha 1181/25 or equiv.

Pin	Function	Wire Color
1	+15 input	RED
2	Power supply common	BLACK
3	-15 input	WHITE
4	+5 input	GREEN
5	+12 output	ORANGE
6	Common	GRAY
7	Interrogation pulse 1	BROWN
8	+15v axis 1	PINK
9	Return pulse 1	YELLOW
10	-15v axis 1	VIOLET
11	Common	TAN
12	Interrogation pulse 2	BLUE
13	+15v axis 2	RED/BLACK
14	Return pulse 2	RED/YELLOW
15	-15v axis 2	RED/GREEN
16	Common	WHITE/BLACK
17	Interrogation pulse 3	WHITE/BLUE
18	+15v axis 3	WHITE/RED
19	Return pulse 3	WHITE/YELLOW
20	-15v axis 3	WHITE/GREEN
21	Common	WHITE/GRAY
22	Interrogation pulse 4	WHITE/BROWN
23	+15v axis 4	WHITE/ORANGE
24	Return pulse 4	WHITE/BLACK/RED
25	-15v axis 4	WHITE/VIOLET

Ordering Information

Part Number: TMC 188/40.

One set of cables is provided with each module.

Contact: Herb Johanson at (206) 254 8688

Accessories and Products for the 505

Part Number	Description
TMC 188/40	Motion controller using magnetostrictive sensors
TMC 188/40-Q	Motion controller using quadrature sensors
TMC 188/40-TA	Motion controller coordinated with analog sensors (i.e., pressure control applications using magnetostrictive sensors)
TMC 188/40-QA	Quadrature Encoder motion controller coordinated with analog sensors.
SSS/10	1 axis Servo System Simulator
AMP/10	1 axis RS422 converter(two required)
MCCBS	6 ft cable set (DB15P and DB25P with pigtails)
MCCBS-01	6 ft DB15P cable with pigtails
MCCBS-02	6 ft DB25P cable with pigtails
MCCBS-03	10 ft DB37P-Q cable with pigtails
MCCBS-04	10 ft DB37P-A cable with pigtails

Company Profile

Delta Computer Systems, Inc. manufactures motion controllers and other industrial controls providing high performance automation solutions to a wide range of industries.

Temposonics is a trademark of MTS Systems, Inc.

